

Product data sheet

Specifications



Easergy P3L30 line protection

P3L30

Main

Range of product	Easergy P3
Relay application	Line differential
Product reference	P3L30
Device mounting	Flush
Mounting support	Rack
Mounting mode	Flush mounting
Power supply	110...230 V AC/DC 50/60 Hz tolerance: + 10 % - 15 % 24...48 V AC/DC 50/60 Hz tolerance: + 10 % - 15 %
Measuring inputs	: 1/5 A CT 36 : 1/0.2 A CT
Number of Digital Outputs (DO)	22 digital
Communication protocols	TCP/IP all counters conforming to 60255-5 DNP3 - DNP3 TCP DeviceNet Ethernet IP/Modbus TCP Modbus RTU Profibus DP SPAbus
Redundancy communication port protocol	PRP RSTP
Cybersecurity	Enable/disable communication ports Firmware signature Password protection Port hardening Role-based access control
Protection functions	Phase overcurrent 50/51 Phase overcurrent 50/51 22 Directional phase overcurrent 67 Earth fault overcurrent 50N/51N Directional earth fault 67N Transient earth fault 67NI Capacitor bank unbalance 51C Current protection 46 I2/I1 Cold load pick-up CPLU 50/51 Harmonic distortion 50/51 Circuit breaker protection 50 BF Switch ON to fault (SOTF) 50/51 Underload 32P Fault locator 21FL Recloser 79 Undercurrent 37 Thermal overload for feeder 49T Capacitor overvoltage 59C Negative sequence overcurrent 46 Overvoltage (L-L or L-N) 59 Undervoltage (L-L or L-N) 27 Positive sequence undervoltage 27P Earth fault overcurrent 51N/51G

Underfrequency 81
 Overfrequency 81O
 Rate of change of frequency 81R
 Synchro-check 25
 Lockout 86
 CT supervision 60
 VT supervision 60
 Programmable stages 99
 Programmable curve 99
 Logic selectivity
 Differential protection 87B

Relay type	Multifunction control relay
Controllable switchgear devices	6 controlled + 8 displayed
Number of setting groups	User
Monitoring functions	Trip circuit supervision 74 Circuit breaker monitoring Relay self-monitoring
Switchgear diagnosis type	Cumulative breaking current (2 configurable buttons) Trip circuit supervision Nb of operations, operating time, charging time, nb of racking out operations VT supervision CT supervision
Connections - terminals	Clamps terminal flush mounting Ring lugs

Complementary

Maximum power consumption in W	20 W typical 28 W maximum
Input power interruption	50 ms
Time synchronisation protocol	SNTP IRIG-B
Software name	Easergy SmartApp ESetup Easergy Pro
Number of key	2 contextual key 1 home 1 for LED test 1 local/remote 5 for navigation 2 for switchgear control
Local signalling	2 x LED red status and alert 16 x LED green/red/orange programmable
Device connection	Extension port straight Serial port straight Serial port fiber optic Ethernet port straight Ethernet port fiber optic
Communication compatibility	IEC 61850 Modbus RTU DNP3 IEC 60870-5-103 IEC 61850 goose message Modbus TCP/IP Modbus
Standards	EN 60255-26 EN 60255-27
Height	177 mm total:
Width	264 mm total:
Depth	208 mm total:
Net weight	4.2 kg minimum

Environment

IP degree of protection	IP54 conforming to IEC 60529
Relative humidity	at -40...60 °C

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Recommended replacement(s)